

Specifications

Product Codes	1100MN: natural gas / 1100MP: propane
Product type	Direct Vent, Zero Clearance.
Input (BTU)	30,000 / 16,000, both fuels
Vent Outlet	4 x 6-5/8" co-axial. Top outlet. Rear facing outlet with elbow. Vertical rise at unit required.
Venting System	Co-axial 4 x 6-5/8". Co-Linear 3x4. Minimum vertical rise at unit: 12".
Gas convertible	Yes
Valve	GV60
Control	SYMAX Valor10 remote control or Remote Battery & Wall Switch Kit (included).
Batteries	Fireplace: Yes, in Remote Battery & Wall Switch Kit; Remote control handset: Yes
Electrical	Optional, via V-module to operate remote control and wifi.
Lighting	No
Wifi	¹ Optional. Operated by Valor10 mobile application on smartphone.
Fan (Blower)	Optional, v-module included with kit. Operated by remote control and wifi.
HeatShift	Optional. 5" outlets at fireplace. Uses any LDK kits except LDK8 30" plenum.
Liners	Valor red bricks, LedgeStone, Fluted black, Black, Reflective glass, Herringbone.
Fuel beds	Logs: Driftwood, Birch, Traditional.
Fronts / Trims	Yes.
Outdoor Installation	Yes, with no electrical power connection. Requires GV60CKO Outdoor Conversion kit.
Comments	¹ Wifi requires V-module and electrical power.