

Specifications

Product Codes	700MN: natural gas / 700MP: propane	700XN: natural gas / 700XP: propane
Product type	Direct Vent, Insert. Requires existing, unaltered, solid-fuel burning functioning fireplace/chimney.	
Input (BTU)	700M: NG 26,000 / 13,000 Propane 26,000 / 11,000	700X: 24,000 / 13,000, both fuels
Vent Outlet	Co-Linear AutoFire Vent Plate, 3x3	
Venting System	Co-Linear 3x3, Roof termination. Optional wall termination w/720WSK	
Gas convertible	Yes	
Valve	GV60	
Control	ValorMAX remote control; optional Remote Battery & Wall Switch Kit or Wall Switch Kit	
Batteries	Fireplace: Yes, in battery box; Remote control handset: Yes Optional Remote Battery & Wall Switch Kit	
Electrical	Optional, via v-module to operate remote control and optional fan.	
Lighting	No	
Wifi	No	
Fan (Blower)	¹ Optional, v-module included with kit. Operated by remote control.	
HeatShift	No	
Liners	Ledgestone, Reflective glass, Fluted, Valor Red Bricks	
Fuel beds	Logs: Traditional, Driftwood*, Birch. *Driftwood different than 700X	Logs: Driftwood*; Glass: Murano *Driftwood different than 700M
Fronts / Trims	Yes	
Outdoor Installation	700M ONLY. No electrical connection allowed. Requires GV60CKO Outdoor Conversion Kit.	
Comments	¹ Fan installs at the back of fireplace. Easier to do it first.	