Valor Portrait Dec 2022 1/2 546 Ledgeview ZC / Framing Wall Finish 6-1/8" (154 mm) 32" (813 mm) cement board to header supplied Note -There is a 1" (25 mm) gap between bottom of cement board and top of backing frame assembly 26-7/8" (684 mm) to cement board Note -This is the framing Finished surface of floor width. Drywall to or hearth/shelf, if used, 24" (610 mm) wide must be min. 1-1/2" (to edge of stud brackets) lower than bottom of appliance otherwise the front trim will not fit Minimum 12-3/4" (324 mm) (Allow extra if using rear vent elbow)

S46 Ledgeview ZC / Wall Finish

Dec 2022 2/2

Adjustability of the Ledgeview Front ZC

- Method 1. The appliance's position within the framing cavity may be adjusted forward in the framing up to 1" to accomodate additional wall finish thickness "tucked" behind the backing plate.
- Method 2. The Backing Plate is also adjustable to accomodate up to an additional 3/4" of tile or other non-combustible material over top of the 1/2" non-combustible wall board.
- Method 1 and Method 2 may be combined for a total of 1-3/4" of non-combustible material over top of the 1/2" wall board.

Attention!

When positioning the appliance forward of the framing cavity (Method 1), ensure that the front edge of the backing frame does not protrude beyond the planned finished wall surface. Otherwise the backing plate, when installed, will not sit against the finished wall.

